

New Milford Block & Supply Corp.
574 Danbury Road
New Milford, CT 06776
T 860.355.1101
F 860.355.3772

Montfort Brothers
44 Elm Street
Fishkill, NY 12524
T 845.896.6225
F 845.896.0021

Federal Block
247 Walsh Avenue
New Windsor, NY 12553
T 845.561.4108
F 845.561.5344

SPRING NEWSLETTER 2017

The **Montfort** Group

The purpose of the Montfort Group newsletter is to give all customers more information and keep them updated on the specials we are having for the select seasons.

GREAT NEWS! Come check out some **NEW CAMBRIDGE ARMORTEC PAVERS** for 2017!!

SEE BELOW THE PAVERS MARKED DOWN to 20% OFF:

Sherwood LedgeStone XL Riverbed Blend
Sherwood LedgeStone XL Desert Blend
Sherwood LedgeStone XL Bluestone Blend
Sherwood LedgeStone XL Montauk Blue
Renaissance LedgeStone Bluestone Blend
While supplies last!!

The Montfort Group

Spring/Summer Hours:

Monday through Friday: 7 AM to 4:30 PM

Saturday: 7:30 AM to 12 PM

Sunday: Closed

Warm Weather Construction

Requirements for work in progress:

- Between 100 °F to 40 °F (37.8 °C to 4.4 °C) no special requirements
- Above 100 °F or 90 °F with 8 mph wind (above 37.8 °C or 32.2 °C with a 12.9 km/hr wind)
 - Maintain mortar and grout at a temperature below 120 °F (48.9 °C). Flush mixer, mortar transport container, and mortar boards with cool water before they come into contact with mortar ingredients or mortar. Maintain sand piles in a damp, loose condition. Maintain mortar consistency by retempering with cool water. Use mortar within 2 hr of initial mixing
- Above 115 °F or 105 °F with a wind velocity over 8 mph (46.1 °C or 40.6 °C with a 12.9 km/hr wind)
 - Use cool mixing water for mortar and grout. Ice must be melted or removed before water is added to other mortar or grout materials
 - Comply with all warm weather requirements below